

Index

Symbols

(* ,G) routing table entry 169

(S,G) routing table entry 169

A

AAA (Authentication, Authorization, and Accounting) 219–224

Access Control Lists (ACLs) 28, 30–31, 35, 217–219

access-mode option 121, 143

ACLs (Access Control Lists) 28, 30–31, 35, 217–219

Active state 6

Address Family Identifier (AFI) 5

Administrator field 88

advanced community lists 31

advertising

with Label Distribution Protocol (LDP) 64–67

peer discovery and 74

advertising labels 62

advertising routes

commands used for 6

configuring Border Gateway Protocol (BGP) for 17–23

AFI (Address Family Identifier) 5

aggregation

Border Gateway Protocol (BGP) 38–42

link 206–209

answers for practice exams

advanced options, A-Series switches 247–248

Border Gateway Protocol (BGP) 59–60

multicast routing 198–200

Multi-Protocol Label Switching Layer 2 Virtual Private Network (MPLS L2VPN) 133–134

Multi-Protocol Label Switching Layer 3 Virtual

Private Network (MPLS L3VPN) 110–112

Multi-Protocol Label Switching (MPLS) 83–84, 156–158

Virtual Private LAN Service (VPLS) 156–158

AS (autonomous system) 2

A-Series devices

commands, route advertisements 6

community list values supported by 31

dynamic label allocation 65

route selection, Border Gateway Protocol (BGP) 10

AS-Path Access Controls Lists (ACLs) 30–31

AS_PATH attribute 8

Assert messages 165

Assigned Number field 88

asterisk 30

(* ,G) routing table entry 169

attribute length, total path 4

Authentication, Authorization, and Accounting (AAA) 219–224

autonomous system (AS) 2

B

basic community lists 31

BFD (Bidirectional Forwarding Detection) 50–52

BGP (Border Gateway Protocol)

advertising labels 62

configuring and verifying 11–23

configuring with Kompella method 146–150

described 2–6

exam objectives 1

practice test 55–60

route filtering and policy manipulation 23–38

routing updates 6–10

scaling and stabilizing 38

BGP Finite State machine 5–6

Bidirectional Forwarding Detection (BFD) 50–52

Bidirectional Mode (BIDIR-PIM) 168–169

BIDIR-PIM (Bidirectional Mode) 168–169

Bootstrap Router (BSR) 168, 179–182
Border Gateway Protocol (BGP)
 advertising labels 62
 configuring and verifying 11–23
 configuring with Kompella method 146–150
 described 2–6
 exam objectives 1
 practice test 55–60
 route filtering and policy manipulation 23–38
 routing updates 6–10
 scaling and stabilizing 38
broadcast data transmission 160
BSR (Bootstrap Router) 168, 179–182

C

CAR (committed access rate) 232
caret 30
CBQ (Class-Based Queuing) 236–240
CCC (Circuit Cross Connect) 114
Circuit Cross Connect (CCC) 114
Class-Based Queuing (CBQ) 236–240
clusters 45
committed access rate (CAR) 232
Community attribute 9
community lists 31–32
confederations 42–53
congestion avoidance 232
congestion management 232
connect state 5
Constraint-based LDP (CR-LDP) 68
Control Word field 116–117
CR-LDP (Constraint-based LDP) 68

D

Dampening, Route 46–50
Data Link layer (Layer 2) technologies 201–217
data, NOTIFICATION message 4
Dense Mode (PIM-DM) 165, 179–182

deny all behavior 34
designated forwarder (DF) 169
Designated Router (DR) 164, 167–169
DF (designated forwarder) 169
discovery, neighbor 165
dollar sign 30
Downstream On-Demand mode 74
Downstream Unsolicited mode 74
DR (Designated Router) 164, 167–169
dynamic label allocation, A-Series devices 65

E

eBGP peering 3
Edge Label Switch Router (LSR) 62
Egress value 77
encapsulation command 120, 143
error code, NOTIFICATION message 4
error subcodes, NOTIFICATION message 4
Established state 2, 6
Ethernet mode 121, 143
Ethernet networks, multicast routing 162–163
exam objectives
 advanced options, A-Series switches 201
 Border Gateway Protocol (BGP) 1
 multicast routing 159
 Multi-Protocol Label Switching Layer 2 Virtual Private Network (MPLS L2VPN) 113
 Multi-Protocol Label Switching Layer 3 Virtual Private Network (MPLS L3VPN) 85
 Multi-Protocol Label Switching (MPLS) 61, 135
 Virtual Private LAN Service (VPLS) 135
exams for practice
 advanced options, A-Series switches 245–248
 Border Gateway Protocol (BGP) 55–60
 comprehensive 249–280
 multicast routing 195–200
 Multi-Protocol Label Switching Layer 2 Virtual Private Network (MPLS L2VPN) 129–134

- Multi-Protocol Label Switching Layer 3 Virtual Private Network (MPLS L3VPN) 106–112
 - Multi-Protocol Label Switching (MPLS) 79–84
 - EXP field 62
 - Export VPN target 89
 - expression characters 30
- F**
- FEC (Forwarding Equivalence Class)
 - described 62
 - labels for 76
 - FIB (Forwarding Information Base), IP 63
 - filtering, route 23–38
 - forwarders, Designated (DF) 169
 - Forwarding Equivalence Class (FEC)
 - described 62
 - labels for 76
 - Forwarding Information Base (FIB), IP 63
 - forwarding range, multicast 173
- G**
- goals for exams
 - advanced options, A-Series switches 201
 - Border Gateway Protocol (BGP) 1
 - multicast routing 159
 - Multi-Protocol Label Switching Layer 2 Virtual Private Network (MPLS L2VPN) 113
 - Multi-Protocol Label Switching Layer 3 Virtual Private Network (MPLS L3VPN) 85
 - Multi-Protocol Label Switching (MPLS) 61, 135
 - Virtual Private LAN Service (VPLS) 135
 - Graceful Restart
 - Border Gateway Protocol (BGP) 52–53
 - Label Distribution Protocol (LDP) support 77
 - Graft messages 165
- H**
- headers, MPLS 62
 - hold time 4
 - Hold timer 50
 - hop popping 63
- I**
- iBGP peering 3
 - identifiers
 - Border Gateway Protocol (BGP) 4
 - LSR-ID, assigning 72–77
 - Peer-ID 74
 - VsilD 145
 - Idle state 2, 5
 - IDs
 - Border Gateway Protocol (BGP) 4
 - LSR-ID, assigning 72–77
 - Peer-ID 74
 - VsilD 145
 - IETF (Internet Engineering Task Force Request for Comments) 2
 - IGMP (Internet Group Membership Protocol)
 - configuring 173–175, 190
 - described 164
 - IGP attribute 8
 - import-route command 6
 - Import VPN target 89
 - Ingress value 77
 - Inner VC label 116
 - In/Out Label column 76
 - Intelligent Resilient Framework (IRF) 241–244
 - Internet Engineering Task Force Request for Comments (IETF) 2
 - Internet Group Membership Protocol (IGMP)
 - configuring 173–175, 190
 - described 164
 - Internet Protocol (IP) addresses
 - loopback interface 3
 - multicast routing 162–163
 - Internet value 31
 - IP Forwarding Information Base (FIB) 63
 - IP (Internet Protocol) addresses

- loopback interface 3
- multicast routing 162–163
- ip-prefix argument 72
- IP prefix lists 28–29
- IP Security Virtual Private Network (IPSec VPN) 225–232
- IPSec VPN (IP Security Virtual Private Network) 225–232
- IRF (Intelligent Resilient Framework) 241–244

K

- KEEPALIVE message 4, 6
- KEEPALIVE timer 50
- Kompella method
 - configuring Border Gateway Protocol (BGP) 146–150
 - configuring common parameters 119, 141
 - configuring L2VPN 123–128
 - described 115
 - scalability 137

L

- Label Advertisement Mode 74
- label allocation (dynamic), A-Series devices 65
- Label Distribution Protocol (LDP)
 - advertising labels 62
 - configuring with Martini method 142–146
 - establishing within Multi-Protocol Label Switching (MPLS) networks 64–67
 - Graceful Restart support 77
- Label-Forwarding Information Base (LFIB) 63
- Label Information Base (LIB) 63
- label pop 63
- label push 62
- label swap 63
- Label-Switched Path (LSP)
 - described 63
 - enabling 72–77
- Label Switch Router (LSR) 62

- Label value 62
- Layer 2 (Data Link) technologies 201–217
- LDP (Label Distribution Protocol)
 - advertising labels 62
 - configuring with Martini method 142–146
 - establishing within Multi-Protocol Label Switching (MPLS) networks 64–67
 - Graceful Restart support 77
- Leave Group message 164
- LFIB (Label-Forwarding Information Base) 63
- LIB (Label Information Base) 63
- link aggregation 206–209
- LinkId value 146
- Local Preference attribute 9, 38
- loopback interface IP address 3
- LSP (Label-Switched Path)
 - described 63
 - enabling 72–77
- lsp-trigger all command 64–65
- lsp-trigger command 72
- LSR-ID, assigning 72–77
- LSR (Label Switch Router) 62

M

- MAC addresses, multicast routing 162–163
- MAC address reclaim message 136
- machines, BGP Final State 5–6
- MAD (multiple active detect) 241–244
- mapping, Source-specific Multicast (SSM) 190–191
- Martini method
 - configuring common parameters 119, 141
 - configuring L2VPN 120–123
 - configuring Label Distribution Protocol (LDP) 142–146
 - described 114
 - scalability 138
- MED (Multi-Exit Discriminator) attribute 9
- message types, Border Gateway Protocol (BGP)

- 3–6
 - MP-BGP (Multi-Protocol BGP)
 - configuring 99–105, 193–194
 - described 89–92
 - MPLS header 62
 - MPLS L2VPN (Multi-Protocol Label Switching Layer 2 Virtual Private Network)
 - configuring and verifying 117–128
 - described 114–117
 - exam objectives 113
 - practice test 129–134
 - MPLS L3VPN (Multi-Protocol Label Switching Layer 3 Virtual Private Network)
 - configuring and verifying 93–105
 - described 86–92
 - exam objectives 85
 - practice test 106–112
 - MPLS (Multi-Protocol Label Switching)
 - configuring and verifying 69–77
 - described 61–69
 - exam objectives 61
 - practice test 79–84, 151–158
 - Virtual Private LAN Service (VPLS) and 135–158
 - MSDP (Multicast Source Discovery Protocol)
 - configuring 191–193
 - described 170
 - MSTP (Multiple Spanning Tree Protocol) 202–206
 - multicast data transmission 161
 - multicast forwarding range, configuring 173
 - multicast routing
 - configuring and verifying 170–194
 - described 159–163
 - exam objectives 159
 - Internet Group Membership Protocol (IGMP) 164
 - Multicast Source Discovery Protocol (MSDP) 170
 - practice test 195–200
 - Protocol Independent Multicast (PIM) 164–169
 - Multicast Source Discovery Protocol (MSDP)
 - configuring 191–193
 - described 170
 - Multi-Exit Discriminator (MED) attribute 9
 - multiple active detect (MAD) 241–244
 - Multiple Spanning Tree Protocol (MSTP) 202–206
 - Multi-Protocol BGP (MP-BGP)
 - configuring 99–105, 193–194
 - described 89–92
 - Multi-Protocol Label Switching Layer 2 Virtual Private Network (MPLS L2VPN)
 - configuring and verifying 117–128
 - described 114–117
 - exam objectives 113
 - practice test 129–134
 - Multi-Protocol Label Switching Layer 3 Virtual Private Network (MPLS L3VPN)
 - configuring and verifying 93–105
 - described 86–92
 - exam objectives 85
 - practice test 106–112
 - Multi-Protocol Label Switching (MPLS)
 - configuring and verifying 69–77
 - described 61–69
 - exam objectives 61
 - practice test 79–84, 151–158
 - Virtual Private LAN Service (VPLS) and 135–158
- ## N
- neighbor discovery 165
 - network command 6
 - Network Layer Reachability Information (NLRI) 4
 - NEXT_HOP attribute 8
 - NLRI (Network Layer Reachability Information) 4

no-advertise value 31
 no-export subconfig value 31
 NOTIFICATION message 4
 NULL label 76

O

objectives for exams
 advanced options, A-Series switches 201
 Border Gateway Protocol (BGP) 1
 multicast routing 159
 Multi-Protocol Label Switching Layer 2 Virtual Private Network (MPLS L2VPN) 113
 Multi-Protocol Label Switching Layer 3 Virtual Private Network (MPLS L3VPN) 85
 Multi-Protocol Label Switching (MPLS) 61, 135
 Virtual Private LAN Service (VPLS) 135
 only-tagged option 121, 143
 OpenConfirm state 6
 OPEN message 3–6
 OpenSent state 6
 Optional Non-Transitive attribute 7
 optional parameter length 4
 optional parameters 4
 Optional Transitive attribute 7
 ORIGIN attribute 8
 Outer LSP label 116

P

parameter lengths, optional 4
 parameters, optional 4
 path attributes 4
 peer advertise-community command 31
 peer discovery, advertisements and 74
 Peer-ID 74
 peering
 Border Gateway Protocol (BGP) 2–6
 Label Distribution Protocol (LDP) 67
 peer next-hop-local command 9
 peers, configuring in Border Gateway Protocol

(BGP) 13–16
 Penultimate Hop Popping (PHP) 63
 PE (Provider Edge) router 62
 per-interface label space 74
 period 30
 permit internet entry 32
 per-platform label space 74
 PHP (Penultimate Hop Popping) 63
 PIM-DM (Dense Mode) 165, 179–182
 PIM (Protocol Independent Multicast)
 configuring 175–182
 described 164–169
 PIM-SM (Sparse Mode) 166–168, 179–182
 PIM-SSM (Protocol Independent Multicast-Source-specific Multicast) 190–191
 plus sign 30
 policy manipulation, Border Gateway Protocol (BGP) 23–38
 popping, hop 63
 port-based option 120, 143
 practice exams
 advanced options, A-Series switches 245–248
 Border Gateway Protocol (BGP) 55–60
 comprehensive 249–280
 multicast routing 195–200
 Multi-Protocol Label Switching Layer 2 Virtual Private Network (MPLS L2VPN) 129–134
 Multi-Protocol Label Switching Layer 3 Virtual Private Network (MPLS L3VPN) 106–112
 Multi-Protocol Label Switching (MPLS) 79–84
 prefix lists 28–29, 35
 Protocol Independent Multicast (PIM)
 configuring 175–182
 described 164–169
 Protocol Independent Multicast-Source-specific Multicast (PIM-SSM) 190–191
 Provider Edge (PE) router 62
 P-Tag 143

pull mode 166
 pw-id option 121

Q

QoS (Quality of Service) 232–240
 Quality of Service (QoS) 232–240
 question mark 30
 questions for practice exams
 advanced options, A-Series switches 245–246
 Border Gateway Protocol (BGP) 55–58
 multicast routing 195–197
 Multi-Protocol Label Switching Layer 2 Virtual Private Network (MPLS L2VPN) 129–132
 Multi-Protocol Label Switching Layer 3 Virtual Private Network (MPLS L3VPN) 106–109
 Multi-Protocol Label Switching (MPLS) 79–82, 151–155
 Virtual Private LAN Service (VPLS) 151–155
 queuing 232, 236–240

R

random early detection (RED) 232
 rate-limiting 232
 RDs (Route Distinguishers) 88–89
 RED (random early detection) 232
 reflectors, route 42–53
 REFRESH message 5
 regular expression special characters 30
 remarking precedence 232
 rendezvous point address (RPA) 169
 rendezvous point link (RPL) 169
 Rendezvous Point (RP) 166–169, 179–182
 Request for Comments (RFC) 1771 2
 reset bgp dampening command 50
 Resource ReserVation Protocol (RSVP), advertising labels 62
 Reverse Path Forwarding (RPF) 164
 RFC 1771 2
 route advertisements

 commands used for 6
 configuring Border Gateway Protocol (BGP) for 17–23

route attributes, Border Gateway Protocol (BGP) 7–9

Route Dampening 46–50

Route Distinguishers (RDs) 88–89

route filtering, Border Gateway Protocol (BGP) 23–38

route length, unfeasible 4

Route Limiting 46–50

Route Policies, Border Gateway Protocol (BGP) 32–38

route reflectors 42–53

routers

 Bootstrap (BSR) 168, 179–182

 Designated (DR) 164, 167–169

 Label Switch (LSR) 62

 Provider Edge (PE) 62

routes

 stale 52

 withdrawn 4

route selection, Border Gateway Protocol (BGP) 10

routing, multicast

 configuring and verifying 170–194

 described 159–163

 exam objectives 159

 Internet Group Membership Protocol (IGMP) 164

 Multicast Source Discovery Protocol (MSDP) 170

 practice test 195–200

 Protocol Independent Multicast (PIM) 164–169

routing updates, Border Gateway Protocol (BGP) 6–10

RPA (rendezvous point address) 169

RP-based tree (RPT) 168–169

RPF (Reverse Path Forwarding) 164

RPL (rendezvous point link) 169
RP (Rendezvous Point) 166–169, 179–182
RPT (RP-based tree) 168–169
RSVP (Resource ReserVation Protocol), advertising labels 62
RSVP-TE (RSVP Traffic Extension) 68
RSVP Traffic Extension (RSVP-TE) 68

S

SAFI (Subsequent Address Family Identifier) 5
SA (source active) message 170
scalability, Kompella vs. Martini methods 137–138
scaling Border Gateway Protocol (BGP) 38
security technologies 217–232
service instances
 configuring with Kompella method 148
 configuring with Martini method 143
S field 62
(S,G) routing table entry 169
Shortest Path Tree (SPT) 166
source active (SA) message 170
Source-specific Multicast (SSM) 190–191
Source-specific Multicast (SSM) mapping, configuring 190–191
Sparse Mode (PIM-SM) 166–168, 179–182
special characters, regular expression 30
SP (strict priority) 233–240
SPT (Shortest Path Tree) 166
SSM (Source-specific Multicast) 190–191
SSM (Source-specific Multicast) mapping, configuring 190–191
stabilizing Border Gateway Protocol (BGP) 38
stale routes 52
states
 Border Gateway Protocol (BGP) 3–6
 Idle vs. Established 2
Static VC (SVC) 114
strict priority (SP) 233–240

subcodes
 error, NOTIFICATION message 4
Subsequent Address Family Identifier (SAFI) 5
summarization, Border Gateway Protocol (BGP) 38–42
SVC (Static VC) 114
s-vid option 121, 143
symbols, regular expressions and wildcards 30

T

tagged option 121, 143
targets, Virtual Private Network (VPN) 88–89, 90
TCP (Transmission Control Protocol) Attack Protection 224–225
test objectives
 advanced options, A-Series switches 201
 Border Gateway Protocol (BGP) 1
 multicast routing 159
 Multi-Protocol Label Switching Layer 2 Virtual Private Network (MPLS L2VPN) 113
 Multi-Protocol Label Switching Layer 3 Virtual Private Network (MPLS L3VPN) 85
 Multi-Protocol Label Switching (MPLS) 61, 135
 Virtual Private LAN Service (VPLS) 135
tests for practice
 advanced options, A-Series switches 245–248
 Border Gateway Protocol (BGP) 55–60
 comprehensive 249–280
 multicast routing 195–200
 Multi-Protocol Label Switching Layer 2 Virtual Private Network (MPLS L2VPN) 129–134
 Multi-Protocol Label Switching Layer 3 Virtual Private Network (MPLS L3VPN) 106–112
 Multi-Protocol Label Switching (MPLS) 79–84
TE (Traffic Engineering) 67–69
timers, KEEPALIVE and Hold 50
total path attribute length 4
Traffic Engineering (TE) 67–69

Transit value 77

Transmission Control Protocol (TCP) Attack Protection 224–225

TTL field 62

Type column 77

Type field 88

U

underscore 30

unfeasible routes length 4

unicast data transmission 159

untagged option 121, 143

UPDATE message

described 4

in Established state 6

Export VPN target 89

inclusion in Well-known Mandatory attribute 7

inserting Community attribute into 9

replacements to NEXT_HOP attribute with 9

Virtual Private Network (VPN) targets in 90

V

Virtual Local Area Network (VLAN) 210–217

Virtual Private LAN Service (VPLS)

configuring and verifying 139–150

described 136–139

exam objectives 135

practice test 151–158

Virtual Private Network (VPN) instances

configuring 95–99

described 87–88

Virtual Private Network (VPN) targets 88–89, 90

Virtual Switch Instance (VSI) 136

VLAN mode 121, 143

VLAN (Virtual Local Area Network) 210–217

VPLS (Virtual Private LAN Service)

configuring and verifying 139–150

described 136–139

exam objectives 135

practice test 151–158

vpn-instance argument 72

VPN (Virtual Private Network) instances

configuring 95–99

described 87–88

VPN (Virtual Private Network) targets 88–89, 90

VsiID 145

vsi option 143

VSI (Virtual Switch Instance) 136

W

weighted fair queuing (WFQ) 233–236

weighted round robin (WRR) 233–240

Well-known Discretionary attribute 7

Well-known Mandatory attribute 7

WFQ (weighted fair queuing) 233–236

wildcards 30

withdrawn routes 4

WRR (weighted round robin) 233–240

X

xconnect command 121, 143